

RED SHIELD WARRANTY



RED SHIELD ROOFING SYSTEM LIMITED WARRANTY

Warranty No: R0055192

FBPCO # KC4352

Square Footage: 1000 s.f.

Building Owner: TOWN OF ADDISON

Building Identification: VITRUVIAN PARK TOLIET BUILDING

Building Address: 3956 VITRUVIAN WAY, ADDISON, TX, 75001-4019

Warranty Period Of: TWENTY (20) Years, Beginning On: 02/18/13

Roofing Contractor: GLEBURNE SHEET METAL (08782)

For the warranty period indicated above, Firestone Building Products Company, LLC ("Firestone"), an Indiana limited liability company, warrants to the Building Owner ("Owner") named above that Firestone will, subject to the Terms, Conditions and Limitations set forth below, repair any leak in the Firestone Roofing System ("System").

TERMS, CONDITIONS AND LIMITATIONS

- Products Covered.** The System shall mean only the Firestone brand roofing membranes, Firestone brand roofing insulations, Firestone brand roofing metal, and other Firestone brand roofing accessories when installed in accordance with Firestone technical specifications by a Firestone-licensed applicator.
- Notice.** In the event any leak should occur in the System, the Owner must give notice in writing or by telephone to Firestone within thirty (30) days of any occurrence of a leak. Written notice may be sent to Firestone at the street address or fax number shown on the reverse side of this Limited Warranty. Evidence of this notice shall be the receipt by Owner of a Firestone Leak Notification Acknowledgement. By so notifying Firestone, the Owner authorizes Firestone or its designee to investigate the cause of the leak.
- Investigation.** If upon investigation, Firestone determines that the leak is not excluded under the Terms, Conditions and Limitations set forth in this Red Shield Roofing System Limited Warranty (the "Limited Warranty"), the Owner's sole and exclusive remedy and Firestone's total liability shall be limited to the repair of the leak. Should the investigation reveal that the leak is excluded under the Terms, Conditions and Limitations, the Owner shall be responsible for payment of the investigation costs. Failure by Owner to pay for these costs shall render this Limited Warranty null and void. Firestone will advise the Owner of the type and/or extent of repairs required to be made at the Owner's expense that will permit this Limited Warranty to remain in effect for the unexpired portion of its term. Failure by the Owner to properly make these repairs in a reasonable manner using a Firestone-licensed applicator and within 60 days shall render this Limited Warranty null and void.
- No Dollar Limit (NDL).** There is no dollar limit placed on warranted leak repairs to the extent such repairs are covered by this Limited Warranty.
- Disputes.** Any dispute, controversy or claim between the Owner and Firestone concerning this Limited Warranty shall be settled by mediation. In the event that the Owner and Firestone do not resolve the dispute, controversy or claim in mediation, the Owner and Firestone agree that neither party will commence or prosecute any suit, proceeding, or claim other than in the courts of Hamilton County in the state of Indiana or the United States District Court, Southern District of Indiana, Indianapolis Division. Each party irrevocably consents to the jurisdiction and venue of the above-identified courts.
- Payment Required.** Firestone shall have no obligation under this Limited Warranty unless and until Firestone and the licensed applicator have been paid in full for all materials, supplies, services, approved written change orders; warranty costs and other costs which are included in, or incidental to, the System. In the event that repairs not covered by this Limited Warranty are necessary in the future, Firestone reserves the right to suspend this Limited Warranty until such repairs have been completed and the licensed applicator and/or Firestone has been paid in full for such repairs.
- Exclusions.** Firestone shall have no obligation under this Limited Warranty, or any other liability, now or in the future if a leak or damage is caused by: (a) Natural forces, disasters, or acts of God including, but not limited to, fires, hurricanes, tornadoes, hail, wind-blown debris, lightning, earthquakes, volcanic activity, atomic radiation, insects or animals; (b) Winds of peak gust speed at or in excess of 55MPH calculated at ten(10) meters above ground using available meteorological data; (c) Act(s), conduct or omission(s) by any person, or act(s) of war, terrorism or vandalism, which damage the System or which impair the System's ability to resist leaks; (d) Failure by the Owner to use reasonable care in maintaining the System, said maintenance to include, but not be limited to, those items listed on the reverse side of this Limited Warranty entitled "Building Envelope Care and Maintenance Guide"; (e) Deterioration or failure of building components, including, but not limited to, the roof substrate, walls, mortar, HVAC units, skylights etc.; (f) Construction generated moisture, condensation or infiltration of moisture in, from, through, or around the walls, copings, rooftop hardware or equipment, skylights, building structure or underlying or surrounding materials; (g) Acid, oil, harmful chemicals, or the reaction between them; (h) Alterations or repairs to the System that are not completed in accordance with Firestone's published specifications, not completed by an approved contractor, and/or not completed with proper notice to Firestone; (i) The design of the roofing system. Firestone does not undertake any analysis of the architecture or engineering required to evaluate what type of System is appropriate for a building and makes no warranty express or implied as to the suitability of its Products for any particular structure; such a determination is the responsibility of the architect, engineer or design professional; (j) Improper selection of materials for the roof assembly or the failure to accurately calculate wind uplift and/or roof loads; (k) Deterioration to metal roofing materials and accessories caused by marine salt water; atmosphere, or by regular spray of either salt or fresh water; or, (l) Change in building use or purpose.
- Transfer.** This Limited Warranty shall be transferable subject to Owner's payment of the current transfer fee set by Firestone.
- Term.** The term of this Limited Warranty shall be for the period set forth above and such term shall not be extended under any circumstances.
- Roof Access.** During the term of this Limited Warranty, Firestone's designated representative or employees shall have free access to the roof during regular business hours. In the event that roof access is limited due to security or other restrictions, Owner shall reimburse Firestone for all reasonable cost incurred during inspection and/or repair of the System that are due to delays associated with said restrictions. Owner shall be responsible for the damage caused by, removal and replacement of any overburdens, superstrata or overlays, either permanent or temporary, excluding accepted stone ballast or pavers, as necessary to expose the system for inspection and/or repair.
- Waiver.** Firestone's failure to enforce any of the terms or conditions stated herein shall not be construed as a waiver of such provision or of any other terms and conditions of this Limited Warranty.
- Governing Law.** This Limited Warranty shall be governed by and construed in accordance with the laws of the State of Indiana without regard to that State's rules on conflict of laws.
- Severability.** If any portion of this Limited Warranty is held by a court of competent jurisdiction to be invalid, void or unenforceable, the remaining provisions shall nevertheless continue in full force.

FIRESTONE DOES NOT WARRANT PRODUCTS INCORPORATED OR UTILIZED IN THIS INSTALLATION THAT WERE NOT FURNISHED BY FIRESTONE. FIRESTONE SPECIFICALLY DISCLAIMS LIABILITY UNDER ANY THEORY OF LAW ARISING OUT OF THE INSTALLATION OF, PERFORMANCE OF, OR DAMAGES SUSTAINED BY OR CAUSED BY, PRODUCTS NOT FURNISHED BY FIRESTONE.

THIS LIMITED WARRANTY SUPERSEDES AND IS IN LIEU OF ALL OTHER WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND FIRESTONE HEREBY DISCLAIMS ALL SUCH WARRANTIES. THIS LIMITED WARRANTY SHALL BE THE OWNER'S SOLE AND EXCLUSIVE REMEDY AGAINST FIRESTONE, AND FIRESTONE SHALL NOT BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL OR OTHER DAMAGES INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS OR DAMAGES TO THE BUILDING OR ITS CONTENTS OR THE ROOF DECK. THIS LIMITED WARRANTY CANNOT BE AMENDED, ALTERED OR MODIFIED IN ANY WAY EXCEPT IN WRITING SIGNED BY AN AUTHORIZED OFFICER OF FIRESTONE. NO OTHER PERSON HAS ANY AUTHORITY TO BIND FIRESTONE WITH ANY REPRESENTATION OR WARRANTY WHETHER ORAL OR WRITTEN.

FIRESTONE BUILDING PRODUCTS COMPANY, LLC

By: Phil LaDuke

Authorized

Signature:

Title:

Director, Quality Assurance

Firestone

13-0000

**BUILDING ENVELOPE CARE AND MAINTENANCE GUIDE
(For Red Shield Warranted Roofing Systems)**

Congratulations on your purchase of a Firestone Roofing System! Your roof is a valuable asset that should be properly maintained. **All roofs and roofing systems require periodic inspection and maintenance to perform as designed and to keep your Limited Warranty in full force and effect.**

1. The roof should be inspected at least twice yearly and after any severe storms. A record of all inspection and maintenance activities should be maintained, including a listing of the date and time of each activity as well as the identification of the parties performing the activity.
2. Proper maintenance and good roofing practice require that ponded water (defined as water standing on the roof forty-eight hours after it stops raining) not be allowed on the roof. Roofs should have slope to drain, and all drain areas must remain clean. Bag and remove all debris from the roof since such debris can be quickly swept into drains by rain. This will allow for proper water run-off and avoid overloading the roof.
3. The Firestone Roofing System should not be exposed to acids, solvents, greases, oil, fats, chemicals and the like. If the Firestone Roofing System is in contact with any such materials, these contaminants should be removed immediately and any damaged areas should be inspected by a Firestone Licensed Applicator and repaired if necessary.
4. The Firestone Roofing System is designed to be a waterproofing membrane and not a traffic surface. Roof traffic other than periodic traffic to maintain rooftop equipment and conduct periodic inspections should be prohibited. In any areas where periodic roof traffic may be required to service rooftop equipment or to facilitate inspection of the roof, protective walkways should be installed by a Firestone Licensed Applicator as needed to protect the roof surface from damage.
5. Some Firestone roofing membranes require maintenance of the surface of the membrane:
 - a. **Smooth-surfaced Firestone APP membranes** should be coated with an approved liquid coating, such as Firestone Aluminum Roof Coating or Firestone AcryliTop applied in accordance with Firestone specifications, in order to maximize the service life of the membrane. If this coating is not applied as part of the initial roofing installation, it should be applied within the first five years after the roof is installed to help protect the membrane from surface crazing and cracking. In addition, this coating should be maintained as needed to re-coat any areas that have blistered, peeled or worn through.
 - b. **Granule-surfaced Firestone APP and SBS membranes** do not normally require surface maintenance other than periodic inspection for contaminants, cuts or punctures. If areas of granular loss are discovered during inspection, these areas should be coated with Firestone AcryliTop or other Firestone-approved coating applied in accordance with Firestone specifications.
 - c. **Gravel-surfaced Firestone BUR membranes** do not normally require surface maintenance other than periodic inspection for contaminants or damage. If areas of gravel loss are discovered during inspection, gravel must be reinstalled into hot asphalt to protect the surface of the membrane. Coatings on smooth surface BUR membranes must be maintained as needed to re-coat any areas that have blistered, peeled or worn through.
 - d. **Firestone EPDM and TPO roofing membranes** do not normally require surface maintenance other than periodic inspection for contaminants, cuts or punctures. Occasionally, approved liquid roof coatings, such as Firestone AcryliTop, are applied to the surface of EPDM membranes in order to provide a lighter surface color. Such coatings do not need to be maintained to assure the performance of the underlying EPDM roof membrane, but some maintenance and re-coating may be necessary in order to maintain a uniform surface appearance.
 - e. **Firestone Una-Clad metal roofing panels and trim** do not normally require surface maintenance other than periodic inspection for contaminants or damage. In addition, periodic cleaning of the surface may be required to remove dirt and maintain the aesthetic appearance of the coated metal. Simple washing with plain water using hoses or pressure spray equipment is usually adequate. If cleaning with agents other than water is contemplated, several precautions should be observed: (1) do not use wire brushes, abrasives, or similar cleaning tools which will mechanically abrade the coating surface, and (2) cleaning agents should be tested in an inconspicuous area before use on a large scale.
6. All metal work, including counter-flashings, drains, skylights, equipment curbs and supports, and other Firestone brand rooftop accessories must be properly maintained at all times. Particular attention should be paid to sealants at joints in metal work and flashings. If cracking or shrinkage is observed, the joint sealant should be removed and replaced with new sealant.
7. Any alterations to the roof, including but not limited to roof curbs, pipe penetrations, roof-mounted accessories, and tie-ins to building additions must be performed by a licensed Firestone Licensed Applicator and reported to Firestone. Additional information and reporting forms for roof alterations are available at www.firestonebpc.com.
8. Should you experience a leak:
 - (a) Check for the obvious: clogged roof drains, loose counterflashings, broken skylights, open grills or vents, broken water pipes.
 - (b) Note conditions resulting in leakage. Heavy or light rain, wind direction, temperature and time of day that the leak occurs are all-important clues to tracing roof leaks. Note whether the leak stops shortly after each rain or continues to drip until the roof is dry. If you are prepared with the facts, the diagnosis and repair of the leak can proceed more rapidly.
 - (c) Contact Firestone Warranty Claims at 1-800-830-5612 as soon as possible...but please don't call until you are reasonably sure that the Firestone Roofing System is the cause of the leak.

Firestone feels that the preceding requirements will assist you, the building owner, in maintaining a watertight roof for many years. Your roof is an investment, and maintenance is essential to maximize your return on this important investment.

Firestone
BUILDING PRODUCTS

NOBODY COVERS YOU BETTER™

250 West 96th Street – Indianapolis, IN 46260

1-800-428-4442 * 1-317-575-7000 * FAX 1-317-575-7100

www.firestonebp.com

STOP

IMPORTANT ROOF INFORMATION

This is a Firestone roofing system under warranty by Firestone Building Products. Damage to the roof system(s) caused by negligence may void this building owner's warranty.

We recommend the following precautions.

1. Minimize foot traffic over the surface of the roof. Protective walk-ways should be installed if there will be regular foot traffic. (Foot traffic more than once each 30 days.)
2. Do not move heavy equipment on the roof surface without adequate protection to the surface.
3. Contact Firestone if the roof will be exposed to solvents, grease, oil or other chemical contaminants.
4. Do not puncture the system(s) to install vents or equipment without first contacting Firestone. (1-800-428-4511)

For more information, refer to the complete Roofing Care and Maintenance Guidelines on the reverse side of the Firestone Warranty or call the Firestone Approved Contractor that installed this roof.

ROOFING
CONTRACTOR:

Firestone
BUILDING PRODUCTS

250 West 96th St.
Indianapolis, Indiana 46260
1-800-428-4442
1-317-575-7000
www.firestonebpco.com

Item #188 08/12 (Replaces 01/12)-01

ASPHALT

TPO

METAL

EPDM

Firestone

BUILDING PRODUCTS

NOW THAT YOU HAVE A NEW FIRESTONE ROOFING SYSTEM...

Congratulations on your purchase of a Firestone Roofing System! Your new roof is a valuable asset and as such should be properly maintained. All components of the building envelope require periodic maintenance to perform as designed. "Building Envelope Care And Maintenance Guide" printed on the back of your Firestone Limited Warranty contains a number of important items to assist you in maintaining a watertight building for many years. These maintenance guidelines recommend that the building envelope be inspected at least twice each year. Although this inspection can be performed by any qualified person selected by you, **Firestone recommends that at least one inspection every year be conducted by the Firestone Licensed Applicator who installed your roof.**

Whenever an inspection of the roof is performed, Firestone recommends that the following items be included:

1 ROOF CONDITIONS REQUIRING PERIODIC INSPECTION:

Periodic inspection of the following items is very important to assure that the Firestone Roofing System has not been exposed to conditions not covered by Firestone's Limited Warranty:

- a. **Roof Traffic & Walkways:** The Firestone Roofing System is designed to be a waterproofing component—not a traffic bearing component of the building envelope. As stated in Firestone's System Design Instructions for all Firestone Roofing Systems, "Walkways help protect the membrane from damage due to necessary roof-top service traffic." Please note that walkways should be maintained at all roof access points, around all mechanical equipment which requires maintenance and at all areas where roof traffic more frequent than once a month is anticipated. **If, because of traffic requirements, walkways need to be installed on your roof, contact your Firestone Licensed Applicator before proceeding.**
- b. **Discharges:** All components of the Firestone roof system must be protected from discharges, such as petroleum products, greases, oils and fats, acids and the like. If the building will have any such discharges, please contact Firestone for suggested methods of protection. **If, because of the presence of chemical discharges, protection measures are recommended, contact your Firestone Licensed Applicator before proceeding.**

- c. **Ponding Water:** Proper maintenance and good roofing practice suggests that ponded water (defined as standing water on the roof forty-eight (48) hours after it stops raining) should not be allowed on the roof. Roofs should have slope to drain and all drain areas should remain clean. **If ponded water areas are observed on the roof that cannot be corrected by periodic cleaning of drain areas, contact your Firestone Licensed Applicator for suggestions.**
- d. **Storms:** The building envelope should be inspected after any severe storm, especially after any storm that involves high sustained winds, heavy wind gusts or tornado-like conditions. All roof surfaces should be inspected for damage caused by wind-blown debris. The roof also should be inspected after any hail or ice storm which could have damaged the roofing system. **If storm-related damage to the roof system is observed, contact your Firestone Licensed Applicator before proceeding.**
- e. **Moisture Infiltration:** It is very important to inspect the roofing system for moisture infiltration from sources excluded by Firestone's Limited Warranty. These sources can include but are not limited to:
 - 1. Latent moisture in a pre-existing roofing system or roof insulation remaining beneath the Firestone Roofing System.
 - 2. Moisture infiltration in or through building walls, copings, mortar joints and roof-top equipment.
 - 3. Condensation of water vapor within the roofing system due to temperature and humidity differentials.

Because inspection for moisture infiltration requires professional roofing experience, Firestone recommends that this inspection be performed by a Firestone Licensed Applicator at least once a year.

2 NON-FIRESTONE MATERIALS:

In some instances, non-Firestone supplied materials are used in conjunction with Firestone Roofing Systems. These materials may include, but are not limited to the following items:

- a. Locally-fabricated sheet metal flashings.
- b. Non-Firestone sealants at roof terminations.
- c. Non-Firestone roof insulations.
- d. Non-Firestone insulation fastening devices, including but not limited to roofing screws, insulation plates, construction adhesives and roofing asphalt.
- e. Preservative-treated wood nailers and blocking.
- f. Roof drains and drain inserts.
- g. Pre-fabricated roof curbs.
- h. Concrete walkway or ballast pavers.
- i. Stone ballast.
- j. Non-Firestone roof coatings.

Because such items are not warranted by Firestone, it is important to establish an ongoing inspection and maintenance program to assure that the performance of non-Firestone materials does not adversely affect the weathertight integrity of the Firestone roofing system. **Sheet metal items** should be checked for weathertightness and re-anchored/recalced as needed. **Nailers and blocking** should be checked for soundness, and replaced or re-secured if necessary. **Roof drains and drain inserts** should be cleared of any debris. **Sealants** should be inspected for shrinking or cracking and replaced as required. The integrity of **roof insulation and insulation attachments** should be verified. **Walkway pavers** should be checked for cracking or splitting and replaced if necessary. **Ballast stone** should be checked for deterioration due to freeze/thaw conditions. In addition, all ballasted roofs should be inspected for localized wind displacement of the ballast, especially along perimeter roof areas. In the event ballast displacement is observed, the ballast should be carefully re-dispersed uniformly and the addition of larger ballast stones should be considered.

3 FIRESTONE PRODUCTS REQUIRING PERIODIC INSPECTION:

Although Firestone products do not necessarily require periodic maintenance to assure long-term performance, periodic inspection is very important to assure that these products have not been exposed to conditions excluded by Firestone's Limited Warranty:

- a. The **Firestone Roofing Membrane** should be inspected for tears or punctures caused by wind storms, falling objects, roof traffic and the like. If the Firestone membrane is supplied with a factory applied coating, such as roofing granules, the coating should be inspected for any discontinuities caused by abrasion from wind, roof traffic or other sources. **Tears, punctures and abrasions to the membrane must be repaired by a Licensed Firestone Applicator using Firestone specified repair procedures.**

In addition, the membrane should be inspected for any contamination from discharges, such as petroleum products, greases, oils and fats, acids and the like. If any such discharges are observed on the membrane, please contact Firestone for suggested methods of protection. If, because of the presence of chemical discharges, protection measures are recommended by Firestone, contact your Firestone Licensed Applicator before proceeding.

- b. **Firestone Wall Flashings** also should be inspected for tears, punctures, abrasion and contamination from discharges, following the same procedures as for the Firestone Roof Membrane.

4 INSPECTIONS AND SAFETY:

Inspection of any building envelope should be undertaken only by qualified persons who are familiar with safe practices, including all applicable occupational health and safety regulations relating to roofing and construction. **Firestone recommends that all roof inspections be performed by a Firestone Licensed Applicator or a similar roofing professional.**

5 ARRANGING FOR PERIODIC INSPECTIONS:

Please note that the cost of periodic inspections, either by your Firestone Licensed Applicator or by any other roofing professional, are not included in the cost of your Limited Warranty. Firestone recommends that you contact your Firestone Licensed Applicator to obtain a proposal for inspection and maintenance services.

6 ADDITION OF PHOTOVOLTAIC (PV), GARDEN, OR SIMILAR SYSTEMS:

Not all roofing systems are configured in a way that allows them to accept photovoltaic (PV) systems, garden systems, or other above-membrane additions. Prior to installing any systems over your Firestone roofing membrane, you must contact Firestone Quality Building Services Group at 1-800-428-4511 for review of the roofing system's readiness for accepting above-membrane systems.

Firestone feels that the preceding recommendations will help you maintain a watertight building for many years. To maximize your return on your building investment, appropriate care is essential. Whenever you have questions concerning your roofing system, do not hesitate to contact your Firestone Licensed Applicator or your local Firestone Sales Representative.

Firestone
BUILDING PRODUCTS
NOBODY COVERS YOU BETTER.™

250 West 96th St. • Indianapolis, IN 46260
1-800-428-4442 1-317-575-7000
www.Firestonebpco.com

International Offices:

Firestone Building Products Europe

Ikaroslaan 75 - 1930 Zaventem, Brussels, Belgium

+32 2 7114450

Firestone Building Products Canada

2835 Argentia Rd., Unit #2

Mississauga, ON L5N 8G6

1-888-292-6265 • 905-363-3150

Firestone Building Products Latin America

8200 NW 52 Terrace, Suite #107

Miami, FL 33166

305-471-0117



This green product printed on recycled paper using Soy Inks.