Kimley-Horn and A	ssociates, Inc. n for Unsignalized Intersection				Priority: 2
Client:	Town of Addison	Date: 1/2/18			
Program:	ADA Self-Evaluation and Transition Plan			P	repared By: CMP
KHA No.:	063543021			C	hecked By: EPE
Corridor :	Belt Line Rd				GPS ID: 188
Project Name:	Intersection of Belt Line Rd and driveway (Lat. 32.9541; L	ong96.8294)			
Town:	Addison				
Item No.	Item Description	Quantity	Unit	Unit Price	Item Cost
	EXCAVATION (ROADWAY)	0	CY	\$ 10.00)
	CONC CURB (TY II)	0	LF	\$ 15.00	
	CONC SIDEWALKS (4")	0	SY	\$ 45.00	
	CURB RAMPS	1	EA	\$ 1,500.00	
	RETROFIT DET WARN SURF (CAST IN PLACE)	0	SF	\$ 50.00	
	REMOVING CONC (SIDEWALKS)	20	SY	\$ 9.00	\$ 180.00
	ELIM EXT PAVE MRK & MRKS	0	LF	\$ 2.80	
TxDOT 666/678	REFL PAV MRK PREP, TY I & TY II (W) 24"(SLD)	0	LF	\$ 8.50	\$-
	REPAVE ROADWAY	0	LS	\$ 5,000.00	\$-
	FIX PONDING	0	LS	\$ 2,000.00	\$-
	FIX CURB RAMP TRANSITION	0	LS	\$ 2,000.00	
	MEDIAN NOSE MODIFICATION	0	LS	\$ 5,000.00	
	REMOVE TEMPORARY OBSTRUCTION	0	LS	\$ 500.00	
	FIX CURB RAMP COUNTER SLOPE	0	LS	\$ 2,000.00	
Basis for Cost Proje				Subtotal:	• ,
	☑ No Design Completed			neering: (% +/-) 20%	
	Preliminary Design		Cont	ingency: (% +/-) 20%	• • • • • • • •
	Final Design			Estimated Project Cost:	\$ 3,000.00

Project Location



Field Observations

Intersection Issues	Crosswalk				Possible Solutions	
Intersection issues		E	S	W	Fossible Solutions	
Path of travel pavement condition Path of travel running slope is greater than 5% Path of travel cross slope is greater than 2% for stop control approaches Path of travel cross slope is greater than 5% for free-flow approaches Crosswalk width is less than 6' Crosswalk striping condition		All driveway path of travel issues and possible solutions provided in driveway shapefile (TRPEDDRV)				

Curb Ramp Issues		existing ramp)		Possible Solutions	
	1A	2A			
Curb ramp does not exist and is needed					
Curb ramp does not land in crosswalk					
No 4' x 4' clear space at base of curb ramp					
Curbed side is not 90° or has traversable adjacent surface					
Flare cross slope is greater than 10%	Х	Х			
Curb ramp running slope is greater than 8.3%		Х			
Blended transition running slope is greater than 5%					
Cut-thru ramp running slope is greater than 5%				Remove and replace curb ramp	
Curb ramp cross slope is greater than 2%	Х	Х			
Cut-thru ramp cross slope is greater than 2%					
Curb ramp width is less than 48"	Х	Х			
Cut-thru ramp width is less than 60"					
Permanent obstruction (>0.25") in curb ramp/landing/flares	Х	Х			
Temporary obstruction (>0.25") in curb ramp/landing/flares					
No textured surface at base of curb ramp	Х	Х		For intersection, commercial driveway, and park ramps, insta	
No color contrast at base of curb ramp	Х	Х		color truncated domes	
Landing area does not exist and is needed					
Landing area is less than 5' x 5' or slopes greater than 2%	Х	Х		Remove and replace landing area	
Curb ramp transition onto roadway is greater than 0.25"					
Counter slope of the gutter or street at the foot of the curb ramp is					
greater than 5%					
Ponding occurs at base of curb ramp					



Ramp 1A



Ramp 2A

Opinion of Probable Construction Cost Disclaimer:

The Engineer has no control over the cost of labor, materials, equipment, or over the Contractor's methods of determining prices or over competitive bidding or market conditions. Opinions of probable costs provided herein are based on the information known to Engineer at this time and represent only the Engineer's judgment as a design professional familiar with the construction industry. The Engineer cannot and does not guarantee that proposals, bids, or actual construction costs will not vary from its opinions of probable costs.

Project Location Map Sources:

Esri, DeLorme, NAVTEQ, USGS, Intermap, iPC, NRCAN, Esri Japan, METI, Esri China (Hong Kong), Esri (Thailand), TomTom, 2013, DigitalGlobe, GeoEye, i-cubed, USDA, AEX, Getmapping, Aerogrip, IGN, IGP, swisstopo, and the GIS User Community