



- PLAN NOTES
1. REFER TO SHEET S-5 FOR GENERAL NOTES AND DETAILS.
 2. PROVIDE BRACING AT ALL CORNERS OR USE 1/2" PLYWOOD FULL HEIGHT, AT ALL THE BUILDING CORNERS AND JOGS IN WALL FOR SHEAR WALLS.
 3. TRUSSES SHALL BE DESIGNED TO CURRENT U.B.C. CODE LOAD REQUIREMENTS.
 4. SEE TRUSS MANUFACTURING REQUIREMENTS SHEET S-4.4 ARCHITECTURAL.
 5. ALL DIMENSIONS AND LAYOUT OF STRUCTURE SHALL BE IN ACCORDANCE WITH THE ARCHITECTURAL REQUIREMENTS.
 6. THE CONTRACTOR MAY USE DESIGN TRUSSES IN LIEU OF THE 2x12'S NOTED.
1. REF. ARCH. FOR FF. ELEVATIONS.

1 SECOND FLOOR FRAMING PLAN
SCALE: 1/8" = 1'-0"
2PLFR1DWG

As2/Al
9/19/98

K.S. ATWAL & ASSOCIATES, INC.
CONSULTING ENGINEERS, STRUCTURAL
6804 E. PARKER ROAD, PARKER, TEXAS 75002
PH (972) 442-0821 FAX (972) 442-5404