



CAUTION UNDERGROUND UTILITIES
 CONTACT UTILITY COMPANIES FOR
 LOCATION PRIOR TO CONSTRUCTION
 ANY DAMAGE TO EXISTING FACILITIES
 WILL BE THE SOLE RESPONSIBILITY
 OF THE CONTRACTOR. ANY REPAIRS
 OR DAMAGES SHALL BE PAID FOR
 BY THE CONTACTOR AT NO EXPENSE
 TO THE OWNER.

LEGEND

	PROP. TYPE "H" INLET (MOD.)
	EXIST. RUNWAY OR TAXIWAY LIGHT
	EXIST. INLET
	EXIST. JUNCTION BOX
	EXIST. ELECTRICAL VAULT
	EXIST. UNDERGROUND POWER
	EXIST. POWER POLE W/ GUY WIRE

634	(G-1) STA. 24+50, 25' LT. CONSTRUCT MITERED END SECTION FOR 2-24" R.C.P. F.L. EL. = 625.41 SEE SHEET 19 FOR DETAILS	(D-1) T/W "A" STA. 30+65, 89' LT. CONSTRUCT TYPE H INLET (MOD.) F.L. EL. = 628.63 GRATE EL. = 632.60 SEE SHEET 24 FOR DETAILS	PVI STA = 30+81 PVI ELEV = 634.88 200' V.C.	PVI STA = 33+65 PVI ELEV = 634.99 50' V.C.	(A-7) STA. 27+57.54, 52.79' LT. CONSTRUCT TYPE B HEADWALL FOR 2-48" R.C.P. F.L. EL. = 626.56 SEE SHEET 26 FOR DETAILS							
634	(G-2) STA. 24+50, 30' LT CONSTRUCT TYPE B HEADWALL FOR 2-24" R.C.P. F.L. EL. = 625.64 SEE SHEET 26 FOR DETAILS	CONST. V-BOTTOM DITCH @ 3.63% SLOPE	PROP. SWALE	CONST. 298 L.F. OF 42 R.C.P. @ 0.5101% SLOPE	(A-6) STA. 30+65, 56.37' LT. CONSTRUCT TYPE "H" INLET RISER W/ TYPE "M" (MOD.) M.H. BOT. SEE SHEET 23 FOR DETAILS GRATE EL. = 633.59 F.L. EL. = 627.64							
630	PVI STA = 23+12.84 PVI ELEV = 627.90 100' V.C.	EXIST. GROUND AT Q OF SERVICE RD.	PROP. SWALE	CONST. 304 L.F. OF 48" R.C.P. @ 0.3552% SLOPE	(A-5) STA. 33+64.68, 60.09' LT. EXIST. TYPE "H" INLET RISER W/ TYPE "M" (MOD.) M.H. BOT. GRATE EL. = 633.59 F.L. EL. = 629.16							
626	PROP. MITERED END SECTION	PROP. HEADWALL	PROP. SWALE	CONST. V-BOTTOM DITCH @ 2.680% SLOPE								
	PROPOSED 20' FLAT BOTTOM DITCH, LT.											
23+00	24+00	25+00	26+00	27+00	28+00	29+00	30+00	31+00	32+00	33+00	34+00	35+00

AS BUILT
 5/18/94
 THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED BY
 TRACY L. TERRILL, P.E.
 70974, DN MAY, 1994.
 OCT 20 1995