

**NOTES:**  
CROSSING PANEL SUPPORT THROUGH THE CROSSING MUST BE UNIFORM. CONCRETE TIE SPACING IS TO BE A MAXIMUM OF 24" CENTER TO CENTER. WOOD TIE SPACING TO BE MAXIMUM OF 19 1/2" CENTER TO CENTER. TIE SPACING MUST BE ADJUSTED TO SUPPORT THE ENDS OF THE PANELS

CROSSING SITE IS TO BE INSPECTED PRIOR TO START OF INSTALLATION TO DETERMINE THAT PROPER DRAINAGE AND SURFACE SUPPORT IS PROVIDED, TRACK GRADE IS UNIFORM AND EXISTING TIES ARE AT LEAST 10' LONG.

IF CONDITIONS WARRANT, SITE IS TO BE OVER-EXCAVATED AND CROSSING DRAINAGE SYSTEM INSTALLED USING COMPACTED, WELL GRADED GRANULAR FILL; SUBBALLAST, GEOTEXTILE AND PERFORATED DRAINAGE PIPE (IF REQUIRED) INSTALLED PER DETAILS OF THIS DRAWING.

ADDITIONAL SITE DRAINAGE INCLUDING PROPER DRAINAGE AT EACH QUADRANT OF CROSSING SHALL BE COMPLETED TO ENSURE CROSSING DRAINAGE.

PRECAST PANELS ARE TO BE HANDLED AND SUPPORTED AT SPECIFIED LIFTING INSERT LOCATIONS ONLY. LIFTING EQUIPMENT AND CONNECTION INSERTS ARE TO BE PROPERLY SIZED TO HANDLE THE LENGTH OF PANELS BEING INSTALLED. RING LIFTING DEVICES ARE AVAILABLE FROM COMPANY WAREHOUSE

APPROACH ASPHALT ROADWAY PAVING IS TO MEET STATE DOT HIGHWAY SPECIFICATIONS AND INSTALLED ACCORDINGLY. ASPHALT IS TO BE INSTALLED WITH PAVER WITH MAXIMUM 3" LIFTS AND LAID PARALLEL TO CROSSING TO MINIMIZE APPROACH SETTLEMENTS.



GEOTEXTILE AND PIPE TO BE INSTALLED ONLY AT LOCATIONS WHERE REQUIRED BY STATE OR LOCAL AGENCIES OR WHERE DESIGNATED BY CHIEF ENGINEER.

GALVANIZED ELASTIC FASTENERS ARE TO BE USED WITHIN THE CROSSING AREA AND ON THE (5) TRANSITION TIES ON EACH SIDE OF THE CROSSING. PANDROL E-CLIPS TO BE USED ON WOOD TIE CROSSINGS AND SAFELOK CLIPS ON CONCRETE TIE CROSSINGS.

ALL RAIL JOINTS IN CROSSING AREA TO BE WELDED, DO NOT INSTALL BOLTED JOINT BARS.


REPORT CROSSING GATE MALFUNCTIONS TO 24 HR UPRR CROSSING HOT LINE AT 1-800-848-8715.

ALL EXCEPTIONS TO THIS PLAN MUST BE APPROVED BY THE CHIEF ENGINEER. 162 B




**INTERIOR JOINTS BETWEEN PANELS MUST REST ON CENTER LINE OF A WOOD OR CONCRETE TIE AS SHOWN**

REQUIRED COMPONENTS	
RING LIFTING DEVICE	410-1371
5/8" TORQUES SCREW FOR WOOD TIES (STD DWG 0452)	130-5400
ELASTOMERIC BEARING PAD FOR 141 LB. RAIL ON WOOD TIES	540-0203
CONFORMAL ELASTOMERIC BEARING PAD FOR 10'-0" CONCRETE TIES	503-6315
CONFORMAL ELASTOMERIC BEARING PAD FOR 8'-6" CONCRETE TIES	503-6312
END RESTRAINT FOR CONCRETE TIES (ONLY)	540-1925



**NOTE:** GEOTEXTILE & PIPE TO BE INSTALLED ONLY AT LOCATIONS WHERE REQUIRED BY STATE OR LOCAL AGENCIES OR WHERE DESIGNATED BY CHIEF ENGINEER.

OPTIONAL COMPONENTS (SET INCLUDES 6 PIECES)	
20' SECTION 6" PERFORATED PIPE	510-3201
6" ADJUSTABLE ELBOW	510-3557
6" PIPE BANDS	510-3379
100' ROLL GEOTEXTILE	550-0119



**UNION PACIFIC RAILROAD ENGINEERING STANDARDS**

**INSTALLATION OF ROAD CROSSINGS WITH PRECAST CONCRETE PANELS**

ADOPTED: DEC. 19, 1987  
REVISED: MARCH 19, 2001  
FILE NO.: 0304D

STD DWG  
**0304D**