



- Notes
1. STEEL COLUMN, SEE STRUCTURAL.
 2. CONCRETE MASONRY UNITS, FILL CELLS WITH HARDROCK CONCRETE.
 3. LAVATORY, AM. STD. NO. 2550.25.
 4. WATER CLOSET - AM. STD. NO. 2122.D10.
 5. FLOOR MOUNTED COMBINATION TOILET/LAVATORY FIXTURE SHALL BE SUPER SECURE #4130 FROM, COLOR TO BE SELECTED BY ARCHITECT.
 6. ELECTRIC WATER COOLER, ELKAY ESWA'S SEMI-REC. MODEL, TO BE SELECTED BY ARCHITECT.
 7. BRASSING WALL, RELOCATE FROM EXISTING FACILITY. VERIFY DIMENSIONS.
 8. WALL HUNG BUNK, VANDAL PROOF. TWO ARE TO BE RELOCATED FROM EXISTING JAIL FACILITY.
 9. RAISED CONCRETE FLOOR, SEE STRUCTURAL.
 10. EXISTING MASONRY WALL - RET. STG. FOR FRAMING.
 11. FLOOR DRAIN - JGSAM. 3000X17 1/4" VANDAL PROOF SCREEN.
 12. URINAL AM. STD. NO. 600.011 1/4" SLOAN NO. 186. FQVY FLOOR.
 13. TOILET PARTITION.
 14. 12X12X3/8 DOUBLE TIER STEEL LOCKERS ON 4" RAISED FLOOR. SHEET 3.
 15. EXHAUST FAN CONTROLLED BY LIGHT SWITCH.
 16. LAVATORY - AM. STD. NO. 2416.026.
 17. STORAGE SHELVES, PER ELEVATION NOTES.
 18. 4" RAISED FLOOR - RET. STG. FOR FRAMING.
 19. DASH AS DETAIL. SEE SHEET 9.
 20. KITCHEN CABINET AND COUNTER TOP.
 21. CABINET ABOVE.
 22. SINK AM. STD. NO. 606.229 1/4" SLOAN NO. 186. FQVY FLOOR. REFRIGERATION SPACE (REFRIGERATOR BY OWNER).
 23. HORIZONTAL SLIDING GLASS WINDOW.
 24. FLOOR RECEPTACLES AND MICROPHONE OUTLETS TO BE MOUNTED ON RAISED FLOOR UNLESS COUNCIL TABLE VERIFY LOCATION AT JOBSITE.
 25. NEW GRATING HALL AND DOOR.

- AIR DEVICES
- * ALL SUPPLY DIFFS SHALL BE 24" X 24" LAY IN TYPE (TITUS T45) EXCEPT AS FOLLOWS:
- RMS 126, 168 & 169 SHALL BE 24" X 24" SURFACE MTD (TITUS T45)
 - RMS 112 & 122 SHALL BE 12" X 12" SURFACE MTD (TITUS T45)
- ALL RETURN DIFFS SHALL BE LAY-IN EGG CR. TYPE (TITUS CORE 51 ONLY)
- ALL EXH. REGS SHALL BE SURFACE MTD. EGG CR. TYPE WITH OBD (TITUS CORE 51)
- * PROVIDE O.B.D. IN EA. SUPPLY DIFFUSER OR DAMPER IN BRANCH TAKE-OFF TO EACH DIFFUSER.

- ELECTRICAL SYMBOLS
- DUPLEX WALL OUTLET
 - ▲ TELEPHONE OUTLET

- GENERAL NOTES
1. CORRIDOR 121 SHALL BE A 1 HR FIRE RATED CORRIDOR. THE WALLS SHALL CONSIST OF 5/8" FIRE RATED GYP. ON 2-1/2" METAL STUDS @ 24" O.C.
 2. TYPICAL NEW WALL CONSTRUCTION SHALL BE 5/8" GYP. ON 2-1/2" METAL STUDS @ 24" O.C. AND SHALL FERT. W/ACE @ THE CEILING UNLESS OTHERWISE NOTED ON PLAN.
 3. ALL CARPETING, CABINET WORK, DOORS, AND WARDROBE TO BE REMOVED SHALL REMAIN THE PROPERTY OF THE CITY. ALL OTHER MATERIALS TO BE REMOVED SHALL BE DISPOSED OF BY THE GENERAL CONTRACTOR.
 4. VERIFY ALL DIMENSIONS GIVEN TO EXISTING CONSTRUCTION.
 5. SEE SHT. 2 FOR NEW ELEC. OUTLET LOCATIONS IN EXISTING BUILDING.



Additions and Alterations to
Addison Municipal Center
 Addison, Texas

The O'Brien Corporation
 ARCHITECTURE & ENGINEERING
 ONE NORTH PARK EAST, SUITE 100
 DALLAS, TEXAS 75201
 214-350-1331

301 HVAC Plan
 1/4" SCALE

NOTE: SEE SHEET N° 10 FOR AIR CONDITIONING REVISIONS IN EXISTING PART OF BLDG.