



- LEGEND**
- ▲ CONES
 - OPPOSING TRAFFIC LANE DIVIDERS (OTLD)
 - DRUMS
 - ▬ TYPE III BARRICADE
 - ▬ LOW PROFILE CONCRETE BARRIER
 - ← LANES TO BE OPEN AT ALL TIMES
 - ⇄ LANES TO BE CLOSED DURING OFF-PEAK HOURS ONLY
 - ▭ DUCT BANK TRENCH
 - ▨ DUCT BANK BORING
 - (N) NON-REMOVABLE
 - (R) REMOVABLE
 - (S) 4" WHITE BROKEN
 - (T) 4" WHITE SOLID
 - (Y) PREVIOUS PAVEMENT MARKINGS
 - (Z) EXISTING RAISED PAVEMENT MARKINGS

- NOTES:**
- ALL LOW PROFILE CONCRETE BARRIERS SHALL BEGIN WITH A TYPE 2 LPCB. END LOW PROFILE CONCRETE BARRIERS WITH A TYPE 2 LPCB WHEN IT CAN BE IMPACTED BY OPPOSING TRAFFIC.
 - CONTRACTOR TO ADD NECESSARY SIGNAGE AS NEEDED ACCORDING TO TMUTCD.
 - CONTRACTOR TO ENSURE THAT EQUIPMENT DOES NOT BLOCK LINE OF SIGHT FOR DRIVERS.


 Signature of Registrant: *M.F. Romanowski* Date: 10/25/13
 FIRM REGISTRATION NUMBER: 312

NO.	REVISION	BY	DATE
HALFF 1201 NORTH BOWSER ROAD, RICHARDSON, TEXAS 75081-2276 TEL (214) 348-8200 FAX (214) 739-0065			
PROJECT	DESIGN	DRAWN	DATE
29350	HALFF	HALFF	OCT. 2013
FILE	SHEET		
29350TCP01-02-02	TCP-3		