





TYPICAL SLOPES & DIMENSIONS (NOT TO SCALE)



- 8" CONCRETE PAVEMENT OR CURB & GUTTER (SEE PLAN/PROFILE SHEETS) (TRANS. METAL TIME PIN.) $\triangle (A)$
 - $^{\otimes}$ 6" CEMENT TREATED BASE (STR-M)(CL 2)
- TYPE II CURB ON 8" CONCRETE PAVEMENT OR TYPE TI CURB & GUTTER (SEE PLAN/PROFILE; SHEETS) Δ ©
- **(** BLOCK SOD AND FURN AND PLACE TPSL(CL 2)(4")
- (E) EMBANK (DC)(TY C)(CL 3)
- (F) 4" REINFORCED CONCRETE SIDEWALK
- **©** INTERLOCKING CONCRETE PAVERS (UNIT PAVERS) WITH EDGE RESTRAINT
- \oplus REMOVE EXIST. CONCRETE CURB AND PAVEMENT (SAW CUT FULL DEPTH)
- (1) REMOVE EXIST. CONCRETE SIDEWALK
- REMOVE EXIST. INTERLOCKING CONCRETE (1)
- (k)REMOVE EXISTING CONCRETE RETAINING WALL
- (L) CONCRETE BLOCK RETAINING WALL (SEE DETAIL SHEETS)(SEE PLAN/PROFILE FOR LOCATIONS AND HEIGHTS)



REMOVAL

PROPOSED CONSTRUCTION

NOTES:

ABBREVIATIONS

PROFILE GRADE LINE **EXISTING** CENTERLINE SAW CUT LEFT (FULL DEPTH) RIGHT CONSTRUCTION ROW RIGHT-OF-WAY JOINT CONC CONCRETE GROOVED LONGI-RIGHT TURN LANE TIDINAL JOINT RTL FXIST, JOINT LTL LEFT TURN LANE

- PAVEMENT CONSTRUCTED AT THE MEDIAN SHALL MATCH THE EXISTING SLOPE OF THE ADJOINING
- PAVEMENT CONSTRUCTED ALONG OUTSIDE LANES SHALL HAVE A CROSS SLOPE THAT VARIES ACCORDING TO THE PROFILE GRADE LINE.
- SEE PLAN/PROFILE SHEETS FOR THE LOCATIONS OF CURB & GUTTER AND 8" CONCRETE PAVEMENT.
- SEE PLAN/PROFILE SHEETS FOR HORIZONTAL LAYOUT OF CURB LINES.
- SEE REMOVAL PLAN SHEETS FOR LOCATIONS OF REMOVAL ITEMS. SHEET 4 OF 4

A REVISED 9/2/97 ₽7



TYPICAL SECTIONS

ADDISON TRANSIT PASS ADDISON, TEXAS



