



NOTE: INSTALL DEEP CUT CONNECTIONS ON SANITARY SEWER AT LOCATIONS SHOWN IN PROFILE

CITY OF ADDISON APPROVED FOR CONSTRUCTION
 BUILDING DEPARTMENT
 DATE: 5/17/80
 CONTRACTOR IS HEREBY INSTRUCTED TO TAKE CARE IN ALL THIS OR EXCEEDING ALL RE-QUIREMENTS OF BOTH NATIONAL AND LOCAL CODES FOR ORDINARY IS APPLICABLE TO HIS WORK. ALL OF THESE REQUIREMENTS SHALL NOT BE CONSIDERED TO RELIEVE RESPONSIBILITY OR EMPLOYER'S LIABILITY TO SUCH CODES.

- NOTES:
1. FIRE HYDRANTS SHALL BE MUELLER CENTURION.
 2. GATE VALVES SHALL BE MUELLER.
 3. WATER LINES SHALL HAVE 42" COVER, MINIMUM, AND CLASS C EMBODIMENT (SAND WRAPPED).
 4. MANHOLES TO BE POURED IN PLACE WITH ASBESTOS CEMENT COLLARS.
 5. CEMENT ENCASE WATER AND SEWER CROSSINGS

Revised Sept. 80
 1. Added 2 F.H.'s
 2. " 8" Gate Valve
 5. " Notes #4 & 5

ADDISON, TEXAS	
ADDISON MUNICIPAL AIRPORT WATER & SEWER PLAN	
Riewe & Wischmeyer, Inc. CONSULTING ENGINEERS DALLAS, TEXAS	DESIGNED: R & W APPROVED: R & W DATE: MAY 80
JOB NO. 7930	SHEET NO. 2013
SCALE: 1"=100'	