

TRASH CHUTE VENT TO EXTERIOR
HEIGHT OF 3'-0" PER NFPA-822003 AND
MANUFACTURERS INSTRUCTIONS

METAL FLASHING UNDER TRASH CHUTE COLLAR

STEEL JOISTS PER STRUCTURAL

GARAGE

GARAGE

ELEV. = 106'-9 1/4"

696'-3 5/8" (696.30')

GARAGE

GARAGE

10'-8 1/4"

PARKING GARAGE PER STRUCTURAL

GARAGE

GARAGE

685'-6 3/4" (685.56')

ELEV. = 696'-1"

EXPANSION JOINT

8" CMU WALL

GARAGE

DISINFECTING & SANITIZING UNIT
FLUSHING HEAD & ACCESS PANEL

EXPANSION JOINT
168 DEG. AUTOMATIC SPRINKLER
HEAD AT HIGHEST INTAKE
ADA BOTTOM HINGED INTAKE

GARAGE

GARAGE

FLOOR SUPPORT AND SQUARE HOLE

674'-9 7/8" (674.82')

ELEV. = 685'-4 1/4"

GARAGE

GARAGE

10'-8 1/4"

EXPANSION JOINT

8" CMU WALL

EXPANSION JOINT
ADA BOTTOM HINGED INTAKE

GARAGE

GARAGE

FLOOR SUPPORT AND SQUARE HOLE

664'-1" (664.08')

ELEV. = 643'-11 3/4" ELEV. = 614'-8"

GARAGE

GARAGE

10'-8 1/4"

EXPANSION JOINT

8" CMU WALL

EXPANSION JOINT
SPRINKLER HEAD REQUIRED AT
FIRST INTAKE ABOVE DISCHARGE
ADA BOTTOM HINGED INTAKE

FLOOR SUPPORT AND SQUARE HOLE
PARKING GARAGE PER STRUCTURAL

653'-4 1/8" (653.34')

ELEV. = 653'-3 1/2"

TRASH ROOM

8" CMU WALL

DISCHARGE DOOR
PER MANUFACTURER
(90 MINUTE RATED)

2-02'-04 3/4"
RFL INSULATED
BY MANUFACTURER
AND THRESHOLD
ROOF DOOR

45" ASSEMBLY
CLOSURE LATCH
AND LABELED
DOOR FRAME

TRASH
COMPACTOR

2 CU YD DUMPFESTER CART
(HARRIES TO COMPACTOR)

GARAGE

GARAGE

ACCESSIBLE BOTTOM HINGE
HATCH • 1ST FLOOR ONLY

2 CU YD CART WITH
CUT DOWN SIDE FOR
ACCESSIBLE TRASH LOADING
(DOES NOT HARRY TO COMPACTOR)

640'-7 1/4" (640.60')

ELEV. = 640'-1 1/4"

1 SECTION • TRASH CHUTE (WESTSIDE GARAGE)

2 TRASH CHUTE

SCALE 1/2"=1'-0"
COPYRIGHT © Beeler, Guest, Owens Architects ALL RIGHTS RESERVED

CONSTRUCTION ISSUE
10-17-2011

BGO
architects
4144 N. Central Expy.
Suite 855
Dallas, TX 75204
214.520.8878
bgoarchitects.com

DATE
08-05-2011
PROJECT
11129
SHEET NUMBER

5.6
TRASH CHUTE

KELLER SPRINGS LOFTS

LOFT APARTMENTS IN ADDISON, TEXAS

REVISIONS
09-19-2011
CITY COMMENT
COORDINATION
10-17-2011



10-17-2011