

DISCLAIMER  
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

Shipping Parts List							
Ship each pole with the following attached: enlarged hand hole, pole cap, fixed arm connection bolts and washers, and any additional hardware listed in the table.							
Nominal Arm Length	30' Poles with Luminaire		24' Poles with ILSN		19' Poles with no Luminaire and no ILSN		
	See note above plus one (or two if ILSN attached) small hand hole, clamp-on simplex		See note above plus one small hand hole		See note above		
Single Mast Arm							
Lf ft.	Designation	Quantity	Designation	Quantity	Designation	Quantity	
50	50L		50S		50		
55	55L		55S		55		
60	60L		60S		60	1	
65	65L		65S		65		
Dual Mast Arm							
Lf ft.	Lc	Designation	Quantity	Designation	Quantity	Designation	Quantity
50	20	5020L		5020S		5020	
	24	5024L		5024S		5024	
	28	5028L		5028S		5028	
	32	5032L		5032S		5032	
	36	5036L		5036S		5036	
55	40	5040L		5040S		5040	
	44	5044L		5044S		5044	
	20	5520L		5520S		5520	
	24	5524L		5524S		5524	
	28	5528L		5528S		5528	
60	32	5532L		5532S		5532	
	36	5536L		5536S		5536	
	40	5540L		5540S		5540	
	44	5544L		5544S		5544	
	20	6020L		6020S		6020	
65	24	6024L		6024S		6024	
	28	6028L		6028S		6028	
	32	6032L		6032S		6032	
	36	6036L		6036S		6036	
	40	6040L		6040S		6040	
65	44	6044L		6044S		6044	
	20	6520L		6520S		6520	
	24	6524L		6524S		6524	
	28	6528L		6528S		6528	
	32	6532L		6532S		6532	
65	36	6536L		6536S		6536	
	40	6540L		6540S		6540	
	44	6544L		6544S		6544	

Foundation Summary Table \*\*

Location Ident.	Avg. N Blow /ft.	No. Each	Drill Shaft *** Length (feet)
BELTLINE RD. AT MIDWAY SW CORNER	10	1	21.9
Total Drill Shaft Length			21.9

Notes:

- \* Supply Option "A" unless otherwise noted
- \*\* Foundations may be listed separately or grouped according to similarity of location and type. Quantities are for the Contractor's information only.
- \*\*\* Decimal lengths in Design Table are to allow interpolation for other penetrometer values. Round to nearest foot for entry into Summary Table.

Shipping Parts List						
Traffic Signal Arms (Fixed Mount) (1 per pole) Ship each arm with listed equipment attached						
Nominal Arm Length	Type IV Arm (4 Signals) *		Luminaire Arms (1 per 30' pole)			
	3 Bracket Assembly * and 4 CGB Connectors		Nominal Arm Length	Quantity		
ft.	Designation	Quantity	8' Arm			
50	50IV		ILSN Arm (Max. 2 per pole) Ship with clamps, bolts and washers			
55	55IV		Nominal Arm Length	Quantity		
60	60IV	1	7' Arm			
65	65IV		9' Arm			
Traffic Signal Arms (80 MPH Clamp-On Mount) (1 per pole) Ship each arm with listed equipment attached						
Nominal Arm Length	Type I Arm (1 Signal)		Type II Arm (2 Signals) *		Type III Arm (3 Signals) *	
	2 CGB CONNECTOR AND 1 clamp w/bolts and washers		1 Bracket Assembly * and 3 CGB connectors, and 1 clamp w/bolts and washers		2 Bracket Assembly * and 4 CGB connectors, and 1 clamp w/ bolts and washers	
ft.	Designation	Quantity	Designation	Quantity	Designation	Quantity
20	20I-80					
24	24I-80		24II-80			
28	28I-80		28II-80			
32			32II-80		32III-80	
36			36II-80		36III-80	
40					40III-80	
44					44III-80	
Traffic Signal Arms (100 MPH Clamp-On Mount) (1 per pole) Ship each arm with listed equipment attached						
Nominal Arm Length	Type I Arm (1 Signal)		Type II Arm (2 Signals) *		Type III Arm (3 Signals) *	
	2 CGB CONNECTOR AND 1 clamp w/bolts and washers		1 Bracket Assembly * and 3 CGB connectors, and 1 clamp w/bolts and washers		2 Bracket Assembly * and 4 CGB connectors, and 1 clamp w/ bolts and washers	
ft.	Designation	Quantity	Designation	Quantity	Designation	Quantity
20	20I-100					
24	24I-100		24II-100			
28	28I-100		28II-100			
32			32II-100		32III-100	
36			36II-100		36III-100	
40					40III-100	
44					44III-100	
Anchor Bolt Assemblies (1 per pole)						
Anchor Bolt Diameter	Anchor Bolt Length	Quantity	Each Anchor bolt assembly consists of the following: Top and bottom templates, 4 anchor bolts, 8 nuts, 8 flat washers, 4 lock washers and 4 nut anchor devices (type 2) per Standard Drawing "TS-FD". Templates may be removed for shipment.			
2 1/2"	5' - 3"	1				

Abbreviations  
Lf= Fixed Arm Length  
Lc= Clamp-on Arm Length (44' Max.)



THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED BY KEVIN P. HOPPERS, P.E. 93669 ON JUNE 1, 2005 ALTERATION OF A SEALED DOCUMENT WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS AN OFFENSE UNDER THE TEXAS ENGINEERING PRACTICE ACT.

*Kevin P. Hoppers*

**STANDARD PLANS**  
Texas Department of Transportation  
Traffic Operations Division

**LONG MAST ARM ASSEMBLY PARTS LIST**

Sheet 4 of 4 LMA (4) - 01

© TxDOT November 2000

STATE DISTRICT	FEDERAL REGION	FEDERAL AID PROJECT	SHEET
4-20-01	6	CM XXXX (XXX)	33
COUNTY	CONTROL	SECTION	JOB
DALLAS	****	**	***
			VA