CONSTRUCTION PLANS

FOR

MIDWAY SQUARE ADDITION

THOMAS L. CHENOWETH SURVEY, ABSTRACT NO. 273

PROJECT GENERAL NOTES

- A. Prior to final acceptance by the Town of Addison:
- 1) A Texas Registered Professional Engineer shall certify that the project was constructed in accordance with the plans and specifications approved by
- The Owner shall provide one (1) reproducible set of as-builts (sealed and certified by a Texas Registered Engineer) and two (2) blueline sets. 2) A one (1) year maintenance bond is required for the subdivision infra-
- 3) Contractor shall demonstrate that the water and sanitary sewer systems meet the proper pressure, bacteria, and mandrel tests. In addition, the Owner shall provide a VHS format video tape of the sanitary sewer. The final tests shall be completed upon the installation of paving and other utilities.
- B. Prior to starting construction, the Contractor shall contact the utility companies to locate existing facilities. These include, but may not be limited to, the following:
 - Town of Addison Lone Star Gas Southwestern Bell Storer Cable Harron Cable Systems


6) T.U. Electric

- C. Prior to beginning construction, the Owner or his authorized representative shall convene a Pre-Construction Conference between the Town of Addison, Consulting Engineer, Contractor(s), Utility Companies and any other affected parties. Notify Bruce Ellis (450-2847) at least 48 hours prior to the time of the Conference and 48 hours prior to beginning of
- D. Any existing pavement, curb, and/or sidewalks damaged or removed will be repaired by the Contractor at their expense.
- E. Lot pins shall be in place during construction and prior to final acceptance. Concrete monuments shall be placed on all boundary corners, block corners, curve points and angle points in public right-of-way. Concrete monuments shall be six (6) inches in diameter and twenty-four (24) inches long. A copper pin one-fourth inch in diameter embedded at least three (3) inches in the monument at the monument at the exact intersection point of the monument. The monuments shall be set at such an elevation that after construction, the top of the monument will be not less than twelve (12) inches below the ground surface.
- F. The Contractor shall stamp a 2-inch "S" in the curb at the location of the sewer service
- G. At intersections that have valley drainage, the crown of the intersecting streets will culminate in a distance of forty (40) feet from the intersecting curb line unless otherwise noted.
- H. Temporary or permanent street barricades shall remain at all points of ingress and egress to prevent public use until such street received final acceptance. 1. Contractor shall obtain a right-of-way permit by the Town of Addison for working
- within the public right-of-way. J. During construction, the Owner shall provide a qualified geotechnical lab to perform materials testing during the construction, at the request of the Town of Addison.
- K. The Contractor shall submit material sheets to the Town of Addison for approval prior to incorporating materials into the job.


DEVELOPER:

MCCUTCHIN PROPERTIES P.O. BOX 802043 DALLAS, TEXAS 75380-2043 TOWN OF ADDISON

DALLAS COUNTY, TEXAS



NOVEMBER, REVISED DECEMBER 6, 1993 REVISED JANUARY 7, 1994




1. DEMOLITION PLAN 2. DIMENSIONAL CONTROL & PAVING PLAN 3. DECELERATION LANE PLAN 4A. GRADING PLAN 4B. EROSION CONTROL PLAN 5. DRAINAGE PLAN 6. WATER / SANITARY PLAN 7. STORM SEWER PROFILES 8. SANITARY SEWER PROFILES 9. MISCELLANEOUS CIVIL DETAILS

10.-19. STANDARD DETAILS

SHEET INDEX

COVER SHEET

FINAL PLAT



& Associates, Inc. CONSULTING CIVIL ENGINEERS - SURVEYORS

(214) 490-7090 (214) 490-7099 FAX

Winkelmann

15602.01