

LIGHT FIXTURE SCHEDULE					
MARK	MANUFACTURER/ MODEL	VOL TAGE	LAMP	DESCRIPTION	FUNCTION
A	SHERIDAN 2)SH82-25M-3-H2-CA10-B- SP25-14-RTC-20-SLR ABS LIGHTING 3-5700-HFM-150MH-240-EL- YMS-CD3-CC-SLV	240	2-250W CMH ED28 3-150W CMH ED17	DOUBLE FIXTURE ROADWAY ASSEMBLY ON ROUND TAPERED STEEL POLE WITH 12" WELDED BASE PLATE, LUG NUT COVERS AND ROADWAY FIXTURES WITH CAST ALUMINUM BALLAST CHAMBER, SPUN ALUMINUM DECORATIVE SKIRT, IES TYPE II, FULL CUT OFF, SILVER FINISH, STAINLESS STEEL HARDWARE, ANCHOR BOLTS PER STRUCTURAL DETAIL AND THREE FLOOD LIGHTS WITH ALUMINUM HOUSING, ALUMINUM DOOR/LENS, DOOR SAFETY CHAIN, STEEL YOKE MOUNT, EGG-CRATE LOUVER AND SILVER FINI.	PONTE BRIDGE ROADWAY 20' POLE WITH TWO STREETLIGHTS AND THREE SPOT LIGHTS
B	SHERIDAN 1)SH82-150M-3-H2-CA10-B- SP15-14-RTC-20-SLR	240	1-175W MH ED28	SINGLE FIXTURE ROADWAY ASSEMBLY ON ROUND TAPERED STEEL POLE WITH , LUG NUT COVERS AND ROADWAY FIXTURE WITH CAST ALUMINUM BALLAST CHAMBER, SPUN ALUMINUM DECORATIVE SKIRT, IES TYPE II, FULL CUT OFF, SILVER FINISH, STAINLESS STEEL HARDWARE AND ANCHOR BOLTS PER STRUCTURAL DETAIL.	BELLA BRIDGE ROADWAY 15' POLE WITH ONE STREET LIGHT
C	BEGA 9801MH BEGA 0908HR 9'-8" HINGED POLE	240	1-50W ED17 MH	SINGLE PEDESTRIAN LEVEL POLE MOUNTED FIXTURE ON 5" TO 3" DIAMETER TAPERED AND HINGED POLE. THE SINGLE FIXTURE ON SPREADER ARM AND POLE EXTENSION HAS FLAT GLASS ANCHOR BOLTS PER STRUCTURAL DETAIL AND SILVER FINISH.	SOUTH PEDESTRIAN BRIDGE 9' 8" TAPERED WITH 5'
D1	BEGA CUS1909-58-311	240	1-CMH39MR1625	METAL HALIDE FLOOD WITH MACHINED ALUMIN CONSTRUCTION, KNUCLE MOUNT, SEALED OPTICAL COMPARTMENT , CLEAR TEMPERED GLASS LENS, TAMPERPROOF DESIGNSILVER FINISH, AND MOUNTED ON SURFACE BALLAST HOUSING OF EXTRUDED ALUMINUM, CAST END CAPS, MULTI-TAP ELECTRIC BALLAST, TAMPER RESISTANT, STAINLESS STEEL MOUNTING SCREWS, SILVER FINISH.	PONTE CABLES SURFACE MOUNT 35 W METAL HALIDE
D2	BEGA CUS1909-58-312	240	1-ES 16 MH	METAL HALIDE FLOOD WITH MACHINED ALUMIN CONSTRUCTION, KNUCLE MOUNT, SEALED OPTICAL COMPARTMENT , CLEAR TEMPERED GLASS LENS, TAMPERPROOF DESIGNSILVER FINISH, AND MOUNTED ON SURFACE BALLAST HOUSING OF EXTRUDED ALUMINUM, CAST END CAPS, MULTI-TAP ELECTRIC BALLAST, TAMPER RESISTANT, STAINLESS STEEL MOUNTING SCREWS, SILVER FINISH.	PONTE CABLES SURFACE MOUNT 35 W METAL HALIDE

LIGHT FIXTURE SCHEDULE					
MARK	MANUFACTURER/ MODEL	VOL TAGE	LAMP	DESCRIPTION	FUNCTION
D3	BEGA CUS-1909-58-312	240	1-ES 16 MH	METAL HALIDE FLOOD WITH MACHINED ALUMIN CONSTRUCTION, KNUCLE MOUNT, SEALED OPTICAL COMPARTMENT , CLEAR TEMPERED GLASS LENS, TAMPERPROOF DESIGNSILVER FINISH, AND MOUNTED ON SURFACE BALLAST HOUSING OF EXTRUDED ALUMINUM, CAST END CAPS, MULTI-TAP ELECTRIC BALLAST, TAMPER RESISTANT, STAINLESS STEEL MOUNTING SCREWS, SILVER FINISH.	
D4	BEGA CUS-1909-58-312	240	1-ES 16 MH	METAL HALIDE FLOOD WITH MACHINED ALUMIN CONSTRUCTION, KNUCLE MOUNT, SEALED OPTICAL COMPARTMENT , CLEAR TEMPERED GLASS LENS, TAMPERPROOF DESIGNSILVER FINISH, AND MOUNTED ON SURFACE BALLAST HOUSING OF EXTRUDED ALUMINUM, CAST END CAPS, MULTI-TAP ELECTRIC BALLAST, TAMPER RESISTANT, STAINLESS STEEL MOUNTING SCREWS AND SILVER FINISH.	
D5	BEGA CUS-1909-59-30/312	240	1-ES 16 MH	METAL HALIDE FLOOD WITH MACHINED ALUMIN CONSTRUCTION, KNUCLE MOUNT, SEALED OPTICAL COMPARTMENT , CLEAR TEMPERED GLASS LENS, TAMPER PROOF DESIGN, SILVER FINISH, AND MOUNTED ON SURFACE BALLAST HOUSING OF EXTRUDED ALUMINUM, CAST END CAPS AND WITH 24 INCH 2 1/4 DIA MACHINED ALUMINUM TUBE, MULTI-TAP ELECTRIC BALLAST.	
E	LIGHTWIELD COOL WHITE LUMENPOWER PLUS v2.0 VERTICAL LINEAR FIXTURE	120 PRI 24V AC	LED	LINEAR BRACKET MOUNTED LED FIXTURE EIGHT FEET LONG WITH EXTRUDED ALUMINUM HOUSING, STAINLESS STEEL HARDWARE, 40 DEGREE BEAM ANGLE, 6500K COOL WHITE LED LAMPS, COMPLETE WITH 24 VOLT POWER SUPPLY IN WEATHER PROFF ENCLOSURE.	PONTE BOTTOM PART OF ARCH SIDE RECESS
F	BEGA 6538MH	120	1-50W ED-17 MH	BRACKET MOUNTED METAL HALIDE WITH CAST ALUMINUM HOUSING, UP TO 12 DEGREE TILT, TEMPERED CLEAR GLASS, STAINLESS STEEL SCREWS, SILICONE RUBBER GASKET, ELECTRONIC BALLAST AND SILVER FINISH.	PONTE UNDER BRIDGE
G	BEGA 2287P	120	1-13W CF TWIN TUBE	WALL MOUNT FLUORESCENT CONSTRUCTED OF DIE CAST AND EXTRUDED ALUMINUM WITH INTEGRAL WIRING COMPARTMENT FOR THROUGH WIRING, DIE CAST ALUMINUM FACE PLATE, CLEAR TEMPERED GLASS WITH TRANSLUCENT WHITE CERAMIC COATING, STAINLESS STEEL CAPTIVE SCREWS AND SILVER FINISH	PONTE UNDER BRIDGE WALL MOUNT

FLOOD LIGHT SCHEDULE				
BRIDGE	POLE	MANUFACTURER/ MODEL	QUANTITY	DESIGNATIONS
PONTE	SA1	BSA 5700-XXX-150MH240-ELYMX-CD	3	3,3,3
PONTE	SA4	BSA 5700-XXX-150MH240-ELYMX-CD	3	3,3,3
PONTE	SA2	BSA 5700-XXX-150MH240-ELYMX-CD	3	3,2,3
PONTE	SA4	BSA 5700-XXX-150MH240-ELYMX-CD	3	1,2,3
BELLA	SA1	BSA 5700-HFM-150MH-240-EL	3	3,3
BELLA	SA3	BSA 5700-HFM-150MH-240-EL	3	3,3



THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED BY DIANNE M. POPKEN, P.E. #41979 ON 04-29-2010. ALTERATION OF A SEALED DOCUMENT WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS AN OFFENSE UNDER THE TEXAS ENGINEERING PRACTICE ACT. THE RECORD COPY OF THIS DRAWING IS ON FILE AT THE OFFICES OF HALFF ASSOCIATES, 1201 NORTH BOWSER ROAD, RICHARDSON, TEXAS, 75081. TYPE PPLM 47-312.

4-28-10

NO.	REVISION	BY	DATE
TOWN OF ADDISON DALLAS COUNTY, TEXAS VITRUVIAN PARK BRIDGES LIGHT FIXTURE SCHEDULE			
1201 NORTH BOWSER ROAD, RICHARDSON, TEXAS 75081-2276 TEL (214) 348-0200 FAX (214) 738-0085			
PROJECT	DESIGN	DRAWN	DATE
27379		AHH	APRIL 2010
FILE	SHEET		
-	E0-01		