					f	ircle, Suite 110 McKinney, TX 75069-8524 972.562.4677 972.542.4366 einfelder.com
STRAIGHT DRILLED SHAFT REPORT						
TO: Town of Addison	<b>PROJECT:</b> Vitruvian Park - Addison, TX					
16801 Westgrove Driv	Infrastructure Phase 1D					
Addison, TX 75001-5190		PROJECT NO.: 99526-5				
Test Date:	8/16/2010					
Technician: P. Kidd		Report No: N/A				
IDENTIFICATION			•			
MARK	P2 **	N2 **				
SHAFT DIAMETER	48"	48''				
PLAN/ACTUAL (in.)	48''	48"				
GROUND SURFACE ELEVATION TOP OF SHAFT ELEVATION <sup>1</sup>	546.8'	546.8'				
DEPTH TO BEARING STRATUM (ft.)	16.4'	16.0'				
DESCRIPTION OF BEARING STRATUM	Gray Shale	Gray Shale				
ENETRATION INTO BEARING STRATUM - *	33.0'	33.0'				
PLAN/ACTUAL (ft.)	23.6'	24.0'				
TOTAL DRILLED SHAFT DEPTH	40.0'	40.0'				
STEEL CASING	48"	48"				
DIAMETER (IN.)/DEPTH (ft.)	14.5	14.5				
PLUMBNESS VARIATION	WITHIN	WITHIN				
	TOLERANCE	TOLERANCE				
	1:30 PM	9:50 AM				
	8:25 AM	12:28 PM				
REINFORCING STEEL CAGE LENGTH (ft.)	42.3'	42.3'				
HORIZONTAL REBAR	Spiral	Spiral				
QUANTITY / SIZE	#4	#4				
VERTICAL REBAR	20	20				
QUANTITY / SIZE	#9	#9				
DOWELS / ANCHOR PLATES IN PLACE	Yes	Yes				
CONDITION OF SHAFT BOTTOM	CLEAN	CLEAN				
BEFORE CONCRETE PLACEMENT	DRY	DRY				
PLACEMENT OF CONCRETE STARTED	9:20 AM	2:25 PM				
LACEMENT OF CONCRETE COMPLETED	9:38 AM	2:39 PM				

## \*\* - Ponte Bridge Abutment #2

Reports to: Clay Barnett

KLEINFELDER

Tan Campe

The results shown on this report are for the exclusive use of the client for whom they were obtained and apply only to the samples tested and/or inspected. They are not intended to be indicative of the qualities of apparently identical products. The use of our name must receive prior written approval. Reports must be reproduced in their entirety.